



SPECIFICATIONS

1. INPUT RANGE: 100-240 VAC
2. FREQUENCY RANGE: 50/60 Hz
3. OUTPUT: 8 VDC (ADJUSTABLE +10% / -25%)
4. MAX. OUTPUT CURRENT: 5.0A
5. MAX. OUTPUT POWER 40W
6. PROTECTION: OVERLOAD, OVERCURRENT, SHORT CIRCUIT
7. OPERATING TEMPERATURE: -30°C to +60°C
8. DIMENSIONS: 3.00" x 9.75" x 2.00"
9. ENCLOSURE RATING: NEMA 3/IP65
10. MOUNTING: FLANGE MOUNT
11. CONNECTIONS: KNOCKOUTS FOR 1/2" CONDUIT
12. STANDARDS: ETL LISTED TO UL 2108 WHEN USED WITH TOKISTAR LIGHTING PRODUCTS
UL RECOGNIZED CLASS 2/EN60950, CE AND RoHS CERTIFIED
13. WEIGHT: 1.94 lbs / 0.88 Kg



TOKISTAR LIGHTING INC.

1015 EAST DISCOVERY LANE
ANAHEIM, CA 92801
TEL: 714 772 7005 FAX: 714 772 7014
email: info@tokistar.com Website: tokistar.com

LDR8-40: 40VA LED DRIVER
INPUT: 100~240VAC / OUTPUT: 8VDC