

Surface Mount Down Lights (ROUND)

The LED Surface Mount Down Light offers a streamlined solution for efficient lighting. Built-in Driver on Board (DOB) technology allows for easy ceiling installation without an external driver. Perfect for enhancing any residential or commercial space.



FEATURES

- DOB technology provides a 120V alternating current source and eliminates the need for traditional LED driver
- Quick & easy to install on standard junction box, ceiling mount with mounting plate
- Temperature rating: -20° to 40°C
- Die-cast aluminum housing
- Smooth and continuous dimming with most ELV dimmers
- Rated for 50,000 hours
- No light bulbs to replace or dispose
- Instant full brightness (including in sub-zero temperatures)
- 80+ CRI
- cETLus listed for wet locations
- 5 years limited warranty

APPLICATIONS

- | | |
|--|--|
| RESIDENTIAL <ul style="list-style-type: none"> • Kitchens • Pantries • Laundry rooms • Under cabinet • In cabinet • Under soffits (Outdoor) | COMMERCIAL <ul style="list-style-type: none"> • Lobbies & hallways • Banquet halls • Elevators & stairways • Retail & restaurants • Under cabinet • In cabinet • Wall mount for regress lighting |
|--|--|

SPECIFICATIONS

Size	6 Inches	8 Inches	10 Inches	12 Inches
Product Code	LVLDL-SR-06-XX-WH-L	LVLDL-SR-08-XX-WH-L	LVLDL-SR-10-XX-WH-L	LVLDL-SR-12-XX-WH-L
Electrical	120V AC			
Input Voltage	120V AC			
Power Consumption	11W	14W	17W	22W
Specs	3000/4000K			
Color Temperature	3000/4000K			
Lumen Output	880WW, 900NW	1000WW, 1050NW	1200WW, 1250NW	1800WW, 1850NW
Efficacy	80WW, 82NW	71WW, 75NW	70WW, 73NW	82WW, 84NW
CRI	80+			
Dimmable	Yes (with most ELV dimmers)			
Beam Angle	120°			
LED	Epistar			
Type	Epistar			
Life Span	50,000 Hours			
Design	Die-cast aluminum housing			
Dimensions (Inches)	6" D x 1" H	8" D x 1" H	10" D x 1" H	12" D x 1" H
Dimensions (Millimeters)	152mm D x 25mm H	203mm D x 25mm H	254mm D x 25mm H	305mm D x 25mm H
Product Material	Die-cast aluminum housing			
Trim Finish	BK: Black, BZ: Bronze, BN: Brushed Nickel			
Operating Temperature	-20°C to 40°C			
Approved Location	Kitchens, pantries, laundry areas, and under soffits (outdoors)			
Mounting	Surface via screw-fixed mounting plate			
Warranty	5 years			
Approvals	cETLus listed for wet locations and Energy Star			

PRODUCT CODES

LVLDL - SR - YY - XX - WH - L

Round LED Surface Mount Down Light

SIZE
06 - 6"
08 - 8"
10 - 10"
12 - 12"

LED Colour
WW: 3000K
NW: 4000K

ROUND TRIM RINGS (Sold Separately)
LVLDL - SR - 06 - TR - XX - L
LVLDL - SR - 08 - TR - XX - L
LVLDL - SR - 10 - TR - XX - L
LVLDL - SR - 12 - TR - XX - L

TRIM RING FINISH
BK: Black, BZ: Bronze, SN: Satin Nickel

DIAGRAM

