

# Uplight (Wattage Adjustable)

Engineered for durability and flexibility, this LED Uplight achieves up to 900 lumens of brightness with adjustable wattage, complemented by a choice of three beam spreads.



## FEATURES

- Adjustable wattage control
- High lumen output
- Durable die-cast aluminum
- Versatile beam spread
- Sleek black finish
- Wide voltage compatibility
- Warm light temperature
- Easy installation design
- Weather-resistant coating
- Long-lasting, 15 years warranty

## APPLICATIONS


- Garden lighting
- Facade lighting
- Pathway safety
- Security lighting
- Sign lighting
- Patio ambiance



## SPECIFICATIONS

<b>Product Code</b>	UP-01-12V-BLK	
<b>Electrical</b>	Input Voltage	9-17V AC/DC
	Power Consumption	0-12W (Adjustable)
<b>Specs</b>	Colour Temperature	3000K
	CRI	85
	Lumen Output	900LM Max.
	Efficacy (LM/W)	83
	Dimmable	No, but wattage adjustable
	IP Rating	IP65
	Beam Angle	24/36/60° (Replacable)
<b>LED</b>	Life Span	50,000 Hours
<b>Design</b>	Dimensions (Inches)	6.4 x 6.7 x 2.9"
	Dimensions (Millimeters)	161 x 177 x 73mm
	Finish	Black powder coating
	Material	Die-cast aluminum
	Operating Temperature	-20 to 40°C
	Approved Location	Outdoor
	Mounting	Via Stake
<b>Warranty</b>	15 years	
<b>Approvals</b>	cETLus	

## DIAGRAM



**NOTE:** Comes with a mounting stake to ensure a hassle-free installation.

## ACCESSORIES



**ACC-3R-BLK**  
3 Inch Riser Black

- 3 inches long
- 1 Male and 1 Female end
- ½ inch NPSM thread
- Cast brass
- Black Finish



**ACC-7R-BLK**  
7 Inch Riser Black

- 7 inches long
- 1 Male and 1 Female end
- ½ inch NPSM thread
- Cast brass
- Black Finish



**ACC-12G-2C-BUR**  
Landscape burial wire, 12G, 2C - 500ft spool

**ACC-12G-2C-BUR-XX**  
Landscape burial wire, 12G, 2C - custom cuts

**NOTE:** A transformer is required. See page 108 to 111.

